

Specification Sheet

Date:	01-02-18	Project:		Remark:
File:	RBPSS-GR11-1.X	Version:	1.2	
Title:	VCO GR11 specs	HW version:	1.2	
REF:				

Power: Voltage +12V / -12V
Current +33mA / -33mA
Connection 2x8 pcb pin header for ribbon wire
The cable should be connected with the red band facing the bottom of the module

Physical: Format EURORACK
Size HP18 (91.30mm. H128.5mm)
Depth 29mm (excl knobs and Ribbon cable)
Weight

Connections: Input 1x 1V/OCT / 3.5mm jack : 1x CV-I input / 3.5mm jack (fixed level)
1x Sync IN (hard sync) / 3.5mm jack : 1x PWM input 3.5mm jack
Output 1x SAW out plm 10V / 3.5mm jack : 1x PULS out plm 10V / 3.5mm jack
1x TRI out plm 10V / 3.5mm jack : 1x SUB PULS out plm 10V / 3.5mm jack

Buttons: 1x FREQ (Coarse) : 1x FINE : 1x PWM
1x SUB-1 : 1x SUB-2 : 1x SUB-3 1x SUB-4 (wave part level adjustment)

Description: Voltage Controlled Oscillator
Frequency range plm 1Hz > 6kHz
Four waveform output
temperature stability: 20 to 30 degrees case temperature, in a range of 3.5 octaves

Others: Product Range: GR-Series

EAN code: 7435124476401



No rights can be deducted from this document. Specified specifications may differ from the actual product.

© 2018 ReBach – www.rebach.eu

